

cTc



CTC CTS

Clamp-on Cylinder Thermostat

- Double insulated
- Bimetallic sensor ensures accurate hot water temperature control
- Wide temperature range
- Surface mounted
- Large, clear adjustable dial
- Cylinder strap and hooks
- Easy to use and quick to install
- Also available in tamperproof



Clamp-on Cylinder Thermostat

The CTC CTS Cylinder Thermostat is configured specifically for the control of domestic hot water cylinders to suit householder lifestyles and can provide energy savings when set between the recommended 60°C - 65°C. Supplied complete with a mounting strap for the cylinder and a spring for the heating pipes, this unit is very easy to fit around either the cylinder or pipe.

The bimetallic sensor ensures accurate hot water temperature control, while the large clear adjustable dial is easy to read and adjustable between 0°C and 80°C. The Cylinder Thermostat can be used to switch directly a wet central heating circulating pump or boiler, or to operate zone valves.

Tamperproof version available.

Technical Data

Clamp-on Cylinder Thermostat	CTC CTS
Operation Range	Min 0°C - Max 80°C
Tolerance	Min $\pm 6^\circ\text{C}$ - Max $\pm 4^\circ\text{C}$
Differential	+/- 4°C
Switch Action	S.P.D.T.
Contact Rating	16(4) A 230V - Volt free contact
Protection	IP40
Max Surface Temperature	110°C
Fixing	Plastic coated spring wire (1800m) with hooks or metal pipe strap