



cTc

EZ 34IR, EZ1IR, EZ 22NI & EZ28NI

2 Port Zone Valve, 22mm & 28mm 3/4" & 1" Compression

- Plug in lead
- Power to Motor LED indicator
- Spring return action
- Manual lever for filling/draining the system
- Replacement quick release actuator available and easy to remove and refit
- Quiet operation, minimum power usage
- Quick and easy to install



2 Port Zone Valve, 22mm & 28mm, 3/4" & 1" Compression

The CTC Controls range of 2 Port Motorised Zone Valves are easy-fit, with a simple clip on/off detachable actuator head and plug in cable.

The Actuator features a power to motor LED indicator. The actuator has also been designed to fit directly onto some other manufacturers valve bodies by using the two screws supplied.

The EZ 34IR, EZ11R, EZ 22NI & EZ28NI spring return valves have been designed to be used in commercial, industrial and domestic central heating systems which, when correctly wired with an appropriate room thermostat, cylinder thermostat and programmer, will control the hot water and central heating in an energy efficient manner.

Technical Data

2 Port Zone Valve, 22mm & 28mm, 3/4" & 1" Compression	EZ 34IR, EZ11R, EZ 22NI & EZ28NI
Supply Voltage	220-240VAC, 50/60Hz
Power Consumption	5W
Cable Length	1m - Plug in Cable (2 metre available)
Fluid Temperature Min-Max	+5°C -+88°C
Operating Temperature	5°C to +50°C
Flow Direction	As per arrow on valve body
Auxiliary Switch Rating	250VAC 4A - Volt Free
Response Opening	12 seconds
Response Closing	5 seconds
Max Static Pressure	8 Bar
Max Close-off Pressure	1 Bar
Complies with	EN60730-1, EN60730-2.7, EMC Directive 2004/108/EC, LVD Directive 2006/95/EC