



cTc



CTC RTM

Mechanical Room Thermostat

- Volt free contacts
- Audible click when dial is turned past current temperature and system is turned on/off
- Surface mounted
- Large, clear adjustable dial
- Easy to use and quick to install



Mechanical Room Thermostat

This CTC RTM mechanical room thermostat is an economical and simple to use room thermostat. Simply turn the mechanical control dial to your desired temperature to control your room temperature.

This unit also produces an audible “click” when you turn the dial past the current temperature so you know when the system is being turned ON or OFF.

This mechanical two wire thermostat is very easy to install and, by having volt free contacts, is suitable for systems with either a combination or normal boiler. If you have a three wire installation, simply cut back and make safe the neutral, and this two wire thermostat will give you years of faithful service.

Technical Data

Mechanical Room Thermostat	CTC RTM
Power Supply	230V AC, 50-60Hz
Temperature setting Range	10°C to 30°C
Current Rating	16(4) Amp - Volt free contacts S.P.S.T.
Terminal Differential	Approx +/- 1.5°C
Operating Temperature Range	0°C to 40°C
Dimensions	L83mm x H83mm x D37mm
Complies with:	EN60730-1, EN60730-2.7, EMC Directive 2004/108/EC, LVD Directive 2006/95/EC